

SEE NOTE A


 \Rightarrow


MULTI-LANE/UNDIVIDED



80' (24 m) O.C. SEE NOTE B

SEE NOTE A





TWO-WAY LEFT TURN



- 1. MARKERS USED WITH DASHED LINES SHALL BE CENTERED IN THE GAP BETWEEN SEGMENTS.
- 2. MARKERS USED ADJACENT TO SOLID LINES SHALL BE OFFSET 2 TO 3 (50 TO 75) TOWARD TRAFFIC AS SHOWN.
- 3. MARKERS THROUGH TANGENTS LESS THAN 500' (150 m) IN LENGTH BETWEEN CURVES SHALL BE INSTALLED AT THE LESSER OF THE TWO CURVE SPACINGS.

LANE MARKER NOTES


- B. REDUCE TO 40' (12 m) O.C. ON CURVES WHERE ADVISORY SPEEDS ARE 10 M.P.H (20 km/h) LOWER THAN POSTED SPEEDS.
- A. USE DOUBLE LANE LINE MARKERS SPACED AS SHOWN.

SYMBOLS

- ---- YELLOW STRIPE
- ⇒ WHITE STRIPE
- ONE-WAY AMBER MARKER
- ONE-WAY CRYSTAL MARKER (W/O)
- TWO-WAY AMBER MARKER

DESIGN NOTES

- 1. DOUBLE LANE LINE MARKERS SHALL BE USED UNLESS SPECIFIED OTHERWISE.
- 2. EXCEPT AS SHOWN ON THE LANE REDUCTION TRANSITION AND FREEWAY EXIT RAMP DETAIL, MARKERS ARE NOT TO BE SPECIFIED ON RIGHT EDGE
- 3. THE EXACT MARKER LIMITS, SPACING, AND COLOR SHOULD BE INCLUDED IN THE PLANS.
- 4. MARKERS SHOULD NOT BE USED ALONGSIDE CURBS EXCEPT FOR EXTREMELY SHORT SECTIONS OF CURBS WHERE NOT MORE THAN TWO MARKERS WOULD BE INVOLVED.



LEFT TURN

All dimensions are in inches (millimeters) unless otherwise shown.

FILE NAME =	USER NAME = gaglianobt	DESIGNED .~	REVISED	- T. RAMMACHER 09-19-94		TYPICAL APPLICATIONS	ļ	F.A.U.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.	
Wi\diststd\22x34\tc11.dgn		DRAWN -	REVISED	-T. RAMMACHER 03-12-99	STATE OF ILLINOIS	DAIGED DE		OTABIT	2759	0505 RS-6	соок	24	19
	PLOT SCALE = 50.000 '/ [N.	CHECKED ~	REVISED	-T. RAMMACHER 01-06-00	DEPARTMENT OF TRANSPORTATION	RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)		SIANI)		TC-11	CONTRACT NO. 60E24		1
	PLOT DATE = 1/4/2008	DATE -	REVISED	-		SCALE: NONE	SHEET NO. 1 OF 1 SHEETS STA. TO ST	TA.	FED. ROAD DIST, NO. 1 ILLINOIS FED. AID PROJECT				